

SAFETY DATA SHEET

AXLH200 ANTIQUAX LARGE HOUSEHOLD

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME AXLH200 ANTIQUAX LARGE HOUSEHOLD
 PRODUCT NO. LH200
 SUPPLIER James Briggs a division of ITW Ltd.
 Salmon Fields
 Royton, Oldham
 England OL2 6HZ
 0161 627 0101
 0161 627 0971

2 COMPOSITION/INFORMATION ON INGREDIENTS

| Name | EC No. | CAS-No. | Content | Classification |
|---|-----------|------------|---------|--------------------------------|
| CINNAMIC ALDEHYDE PQ | 203-213-9 | 104-55-2 | < 1% | Xn;R21. Xi;R38. R43. |
| NAPHTHA (PETROLEUM), HYDROTREATED HEAVY | 265-150-3 | 64742-48-9 | 60-100% | Xn;R65. R10,R66. |
| ORANGE TERPENES | 232-433-8 | 8028-48-6 | < 1% | Xn;R65. Xi;R38. N;R50/53. R10. |

The Full Text for all R-Phrases are Displayed in Section 16

3 HAZARDS IDENTIFICATION

Flammable. Repeated exposure may cause skin dryness or cracking.

CLASSIFICATION R10, R66.

4 FIRST-AID MEASURES

GENERAL INFORMATION

NOTE! Effects may be delayed. Keep affected person under observation. NOTE! Keep affected person away from heat, sparks and flames!

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. Perform artificial respiration if breathing has stopped. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

INGESTION

Remove victim immediately from source of exposure. Rinse mouth thoroughly. NOTE! Keep affected person away from heat, sparks and flames! DO NOT induce vomiting. Get medical attention immediately.

SKIN CONTACT

Remove affected person from source of contamination. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Dry chemicals, sand, dolomite etc. Alcohol resistant foam. Water spray, fog or mist. Carbon dioxide (CO2).

SPECIAL FIRE FIGHTING PROCEDURES

Ventilate closed spaces before entering them. Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Do not scatter spilled material with more water than needed to fight the fire. Be aware of danger for fire to re-start. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Ventilate well. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE

AXLH200 ANTIQUAX LARGE HOUSEHOLD

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Risk of vapour concentration on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented.

STORAGE PRECAUTIONS

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

STORAGE CLASS

Flammable compressed gas storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| Name | Std | LT - ppm | LT - mg/m3 | ST - ppm | ST - mg/m3 |
|---|-----|----------|------------|----------|------------|
| NAPHTHA (PETROLEUM), HYDROTREATED HEAVY | | | 1000 mg/m3 | | |
| ORANGE TERPENES | | 100 ppm | | | |

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Occupational Exposure Limit Use chemical cartridge protection with appropriate cartridge.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Use approved safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes wet or contaminated. When using do not eat, drink or smoke. **DO NOT SMOKE IN WORK AREA!**

9 PHYSICAL AND CHEMICAL PROPERTIES

| | |
|------------|--------------------|
| APPEARANCE | Wax |
| COLOUR | Brown |
| ODOUR | Characteristic |
| SOLUBILITY | Insoluble in water |

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may affect central nervous system and cause headache, discomfort, vomiting or intoxication. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

INGESTION

May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

AXLH200 ANTIQUAX LARGE HOUSEHOLD

SKIN CONTACT

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

EYE CONTACT

Irritating to eyes. Irritation, burning, lachrymation, blurred vision after liquid splash.

HEALTH WARNINGS

Repeated exposure may cause chronic eye irritation. Swallowing concentrated chemical may cause severe internal injury.

ROUTE OF ENTRY

Inhalation. Skin and/or eye contact.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



| | | | |
|----------------------|---|------------------|--|
| UK ROAD CLASS | 4.1 | | |
| PROPER SHIPPING NAME | SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (ORANGE SWEET EXT,) | | |
| UN NO. ROAD | 3175 | UK ROAD PACK GR. | II |
| ADR CLASS NO. | 4.1 | ADR CLASS | Class 4.1: Flammable solids, self-reactive substances and solid desensitized explosives. |
| ADR PACK GROUP | II | HAZARD No. (ADR) | 40 |
| ADR LABEL NO. | 4.1 | HAZCHEM CODE | 1Z |
| CEFIC TEC(R) NO. | 41GF1-II+III | RID CLASS NO. | 4.1 |
| RID PACK GROUP | II | UN NO. SEA | 3175 |
| IMDG CLASS | 4.1 | IMDG PACK GR. | Not Applicable |
| EMS | F-A, S-I | MFAG | See Guide |
| MARINE POLLUTANT | No. | UN NO. AIR | 3175 |
| AIR CLASS | 4.1 | AIR PACK GR. | II |

15 REGULATORY INFORMATION

RISK PHRASES

| | |
|-----|---|
| R10 | Flammable. |
| R66 | Repeated exposure may cause skin dryness or cracking. |

SAFETY PHRASES

| | |
|-----|---|
| S37 | Wear suitable gloves. |
| S51 | Use only in well-ventilated areas. |
| P14 | Contains CINNAMIC ALDEHYDE PQ. May produce an allergic reaction. |
| S2 | Keep out of the reach of children |
| S46 | If swallowed, seek medical advice immediately and show this container or label. |

UK REGULATORY REFERENCES

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.
 The Control of Substances Hazardous to Health Regulations 2002.

EU DIRECTIVES

Dangerous Preparations Directive 1999/45/EEC.
 System of specific information relating to Dangerous Preparations. 2001/58/EEC.

AXLH200 ANTIQUAX LARGE HOUSEHOLD

STATUTORY INSTRUMENTS

The Control of Substances Hazardous to Health Regulations 2002.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations.

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Occupational Exposure Limits EH40.

CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION DATE 06/02/2006

REV. NO./REPL. SDS GENERATED 3

RISK PHRASES IN FULL

| | |
|--------|--|
| R10 | Flammable. |
| R21 | Harmful in contact with skin. |
| R38 | Irritating to skin. |
| R43 | May cause sensitisation by skin contact. |
| R50/53 | Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R65 | Harmful: may cause lung damage if swallowed. |
| R66 | Repeated exposure may cause skin dryness or cracking. |