

SAFETY DATA SHEET

AXQP ANTIQUAX QUICK POLISH

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME: AXQP ANTIQUAX QUICK POLISH

PART No.: XQP

SUPPLIER: James Briggs Ltd
Salmon Fields Industrial Estate
Royton, Oldham
England OL2 6HZ
Tel: 0161 627 0101
Fax: 0161 627 0971

EMERGENCY TELEPHONES: (+0044) (0) 161 620 5400

2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME			CONTENT
CAS No.:	EINECS Nr.:	CLASSIFICATION	
NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT			1-5 %
64742-49-0	265-151-9	Xi ,F ,N R-11, 38, 51/53, 65, 67	
SODIUM NITRITE			0-1 %
7632-00-0	231-555-9	T ,O ,N R-8, 25, 50	
ISOBUTANE			1-5 %
75-28-5	200-857-2	F+ R-12	
BUTANE			1-5 %
106-97-8	203-448-7	F+ R-12	
PROPANE			5-10 %
74-98-6	200-827-9	F+ R-12	
ODOURLESS KEROSENE			1-5 %
64742-47-8	265-149-8	Xn R-65, 66	

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION

Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. FIRST AID MEASURES

GENERAL: Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION:	Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering 100% oxygen. Keep the affected person warm and at rest. Get prompt medical attention.
INGESTION:	DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.
SKIN:	Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.
EYES:	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:	Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
SPECIAL FIRE FIGHTING PROCEDURES:	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.
UNUSUAL FIRE & EXPLOSION HAZARDS:	Aerosol cans may explode in fires.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEANUP METHODS:	Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.
-------------------------------	---

7. HANDLING AND STORAGE

USAGE PRECAUTIONS:	Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.
STORAGE PRECAUTIONS:	Aerosol cans: Must not be exposed for direct sunlight or temperatures above 50°C.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME:	CAS No.:	STD	LT EXP 8 Hrs	ST EXP 15 Min
SODIUM NITRITE	7632-00-0		No std.	No std.
BUTANE	106-97-8	OES	600 ppm	750 ppm
PROPANE	74-98-6		Asphyxiating	Asphyxiating
NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT	64742-49-0	OES	1000 mg/m ³	

INGREDIENT COMMENTS: OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

PROTECTIVE EQUIPMENT:



VENTILATION:	Provide adequate general and local exhaust ventilation.
RESPIRATORS:	No specific recommendation made, but respiratory protection must be used if the general level exceeds the Occupational Exposure Level (OEL). Use chemical cartridge protection with appropriate cartridge.
PROTECTIVE GLOVES:	Use protective gloves.
EYE PROTECTION:	Wear approved chemical safety goggles where eye exposure is reasonably probable.
OTHER PROTECTION:	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
HYGIENIC WORK PRACTICES:	DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. No eating or drinking while working with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Aerosol.
COLOUR:	White.
ODOUR/TASTE:	Characteristic.
SOLUBILITY DESCRIPTION:	Slightly soluble in water.
FLAMMABILITY LIMIT - LOWER(%):	0.8
FLAMMABILITY LIMIT - UPPER(%):	9.0

10. STABILITY AND REACTIVITY

STABILITY:	Normally stable.
CONDITIONS TO AVOID:	Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.
HAZARDOUS DECOMP. PRODUCTS:	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO ₂).

11. TOXICOLOGICAL INFORMATION

INHALATION:	May cause irritation to the respiratory system. Solvent vapours are hazardous and may cause nausea, sickness and headaches. Prolonged inhalation of high concentrations may damage respiratory system.
INGESTION:	May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.
SKIN:	Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.
EYES:	Irritating to eyes. May cause chemical eye burns.
ROUTE OF ENTRY:	Inhalation. Skin and/or eye contact.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:	Dangerous for the environment if discharged into watercourses.
--------------------------------	--

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: Empty containers must not be burned because of explosion hazard. Dispose of in accordance with Local Authority requirements.

14. TRANSPORT INFORMATION

LABEL FOR CONVEYANCE:



UN No. ROAD:	1950
UK ROAD TRANSPORT CLASS:	2.1
UK ROAD PACK GR.:	Not Applicable
ADR CLASS No.:	2
ADR CLASS:	Class 2: Gases; Compressed, liquefied or dissolved under pressure.
ADR PACK GR.	Not Applicable
ADR LABEL No.:	2.1
CEFIC TEC(R) No.:	20G53
PROPER SHIPPING NAME I:	AEROSOLS
RID CLASS No.:	2
RID PACK GR.	Not Applicable
UN No. SEA:	1950
IMDG CLASS:	2.1
IMDG PACK GR.:	Not Applicable
EmS No.:	2-13
MFAG TABLE No.:	See Guide
MARINE POLLUTANT:	No.
UN No., AIR:	1950
ICAO CLASS:	2.1
AIR PACK GR.:	Not Applicable

15. REGULATORY INFORMATION

LABEL FOR SUPPLY:



RISK PHRASES:	R-12 Extremely flammable. R-52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
SAFETY PHRASES:	S-16 Keep away from sources of ignition - No Smoking. S-2 Keep out of the reach of children. S-23C Do not breathe vapour/spray S-51 Use only in well-ventilated areas. S-56 Dispose of this material and its container to hazardous or special waste collection point.
UK REGULATORY REFERENCES:	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. The Control of Substances Hazardous to Health Regulations 2002.
STATUTORY INSTRUMENTS:	Control of Substances Hazardous to Health. Chemicals (Hazard Information and Packaging) Regulations.
APPROVED CODE OF PRACTICE:	Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES:	Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION

PRINTING DATE:	2003-07-17
R-PHRASES (Full Text):	R-65 Harmful: may cause lung damage if swallowed. R-66 Repeated exposure may cause skin dryness or cracking. R-11 Highly flammable. R-38 Irritating to skin. R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-67 Vapours may cause drowsiness and dizziness. R-8 Contact with combustible material may cause fire. R-25 Toxic if swallowed. R-50 Very toxic to aquatic organisms. R-12 Extremely flammable.